TTMA Flange Spacer with 1/2" Port

Size	Description	Aluminum Part #
4"	flange spacer with 1/2" female NPT port	TTFS4AL-FP50

TTMA Flange Extensions

Application

· Used on load arms to connect an API load coupler to a load arm

Features

- Adds a 6" space between the load arm and the tank truck
- · Extension with groove provides a specified parting point to prevent excessive damage to the loading arm

Size	Description	Aluminum Part #
4"	TTMA flange extension	TETF4AL
4"	TTMA flange extension with groove	TETFG4AL
4"	TTMA flange extension with 1/2" female NPT port	TETF4ALFP50

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.



Cam & Groove Adapters x TTMA Flange

Features

- · Aluminum flanges have a flat face; stainless flanges have a raised face
- Reference dixonvalve.com for flange drilling standards
- Pressure rating is based on the seal of the mating part, see ratings on pages 20, 26

Size	356T6 Aluminum Part #	316 Stainless Steel Part #
2" x 3"	2030-ALT-AL	
3"	300-ALT-AL	300-ALT-SS1
3" x 4"	3040ALTAL	
4"	400-ALT-AL	400-ALT-SS ¹
6"	600-ALT-AL	

Parts are produced as a welded fabrication

Cam & Groove Couplers x TTMA Flange

Features

- Supplied standard with a nitrile rubber gasket; other gaskets available on pages 68 71
- Use Dixon® replacement handles only

	356T6 Aluminum
Size	Part #
3"	300-DLT-AL
3" x 4"	3040DLTAL
4"	400-DLT-AL
6"	600-DI T-AI

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.



Pressure rating is based on the seal of the mating part, see ratings on pages 20, 26

Size	356T6 Aluminum Part #
3"	30022ALTAL
4"	40022ALTAL

Cam & Groove 22-1/2° Couplers x TTMA Flange

Features

- Supplied standard with a nitrile rubber gasket; other gaskets available on pages 68 71
- · Use Dixon replacement handles only

	Size	356T6 Aluminum
		Part #
	4"	40022DLTAL

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.



TETF4AL



TETFG4AL





