The state of the s

VR4030CS-AL45

Application

Dixon® Vapor Recovery Couplers

Not intended for liquid service, for vapor recovery only Features



- 'Floating bridge' poppet design allows optimal flow
- Machined hose shank ensures easier insertion into hose and better sealing
- Durable, easy-to-couple stainless cam arms
- · Big wings ensure contact with air interlock button on tanker, helping prevent drive-offs
- Change poppet seal without removing the coupler from the hose
- Secure to hose with traditional band clamps or built in crimp collar
- 4" MNPT version allows for either cam and groove or threaded flange option

Material

· Seal: Nitrile rubber and FKM



VR4040CS-AL

Coupler Size	Description	Aluminum Part #
	4" coupler x 4" hose shank	VR4040CS-AL
4"	4" coupler x 3" 45° hose shank	VR4030CS-AL45
	4" coupler x 4" 45° hose shank	VR4040CS-AL45
	4" coupler x 4" 45° hose shank swivel	VR4040CS-ALS45
	4" coupler x 4" MNPT connection	VR4040CS-4MNPT
	4" coupler x 3" hose shank	VR4030CS-SH

Bayloc Vapor Coupler with Locking Handle

Application

For use in petroleum loading terminals



DBC62LVPR-300

Materials Specification

Body: aluminium
 Maximum operating pressure: 120 PSI

Seals: FKM

Size	Part #
3"	DBC62LVPR-300

NOTE: Must be used with a 4100FNG series check valve



VRHK

Repair Kits

Description	Part #
handle kit	VRHK
compact handle kit	VRHK-C
seal repair kit	VR4040CSRK1
cam arm repair kit	VR4040CSRK2

Couplers x Female NPT

Application

Not intended for liquid service, for vapor recovery only

Materials



- Body: cast aluminum
- Arms: bronze with stainless steel pins
- · Finger rings: plated carbon steel
- Gasket: nitrile rubber



Coupler Size	Female NPT Size	356T6 Aluminum Part #
4"	3"	4030-DVR-AL
	4"	400-DVR-AI

EZ Boss Lock® Vapor Recovery Coupler with Probe x TTMA Flange

New

Materials

- Body: 356T6 aluminium
- Arms: stainless steel EZ Boss-Lock
- · Gasket: nitrile rubber

Coupler Size	Flange Size	356T6 Aluminum Part #
4"	4"	ADLTVR400EZ