



## GHT Ball Valve

### Specifications

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

Description	Required Case Qty	Forged Brass Part #
3/4" male GHT x female GHT	6	GHD-500GHV

## Quick Connects

### Feature

- Easy push-pull ring for long-lasting and quick hose attachments

### Specifications

- Maximum operating pressure: **150 PSI** at ambient temperature **70°F (21°C)**
- Maximum temperature: **140°F (60°C)**

Description	Required Case Qty	Kit Contains Part #	Brass Part #
complete assembly, female GHT coupler x male GHT plug	6	500QCF (2) 500QCM	GHD-500QCK



## Short Shank Fittings

### Features

- Extended male GHT - deeper thread
- Complete coupling set is shipped unassembled

Hose Size	Required Case Qty	Kit Contains Part #	Brass Part #
3/4"	6	5851212C 5881212C	GHD-5891212K



## Menders

Hose Size	Required Case Qty	Kit Contains Part #	Brass Part #
3/4"	6	1781212C (2)	GHD-1781212C



## Sweeper Nozzle

Thread Size	Discharge	Length	Required Case Qty	Brass Part #
3/4" GHT	3/16"	2"	6	GHD-PSN76



## Adjust-A-Power Nozzle

### Application

- Ideal for patio, auto and boat, driveway, and garden

### Features

- Produces 50% more power than twist nozzles
- Does not require a washer
- Leave nozzle in the open position when not in use
- Brass construction with stainless steel bearings

### Specification

- Maximum operating pressure: **100 PSI** (water only) at ambient temperature **70°F (21°C)**

Thread Size	Required Case Qty	Brass Part #
3/4" GHT	6	GHD-AAPN75GHT

