Split Flange Swivels

Applications

 Used in petroleum, blending plants, petrochemical, refining, mining, distilling, paint plants, farm irrigation and fertilizing, wastewater treatment, food and beverage process equipment, and marine

Features

- Bearing pack design allows easy seal change without removing the ball bearings
- Simple maintenance: remove one nose piece, replace seal pack, reinstall with little down-time
- Instream seal separates wetted area from ball bearings allowing for longer bearing pack life over conventional swivels
- Wide set bearing race for higher moment loads
- Compact design for low profile applications

Materials

- · Bearing pack: through hardened forged high carbon alloy
- · Material contact surfaces: stainless steel or carbon steel nose pieces

Specifications

- · Pressure rating: up to 600 PSI
- Temperature: -40°F to 450°F (-40°C to 232°C) depending on seal material (with standard seals: 350°F (177°C)

Available options

- · Stock end configurations: 150 lb. and 300 lb. flanges, FNPT, butt weld, others per request
- Stock seals: Baylast™, FKM, PTFE, others per request
- Full penetration weld
- Contact Dixon® at 888-226-4673 for additional materials and configurations

| Size | Carbon Steel Weld x Weld with Baylast Pressure Seals Part # | Carbon Steel Weld x Weld with FKM Pressure Seals Part # | Carbon Steel 150# Flange x 150# Flange with Baylast Pressure Seals Part # | Carbon Steel 150# Flange x 150# Flange with FKM Pressure Seals Part # |
|------|--|--|--|--|
| 2" | SF220WXWCS00 | SF220WXWCS10 | SF220FGXFGCS00 | SF220FGXFGCS10 |
| 3" | SF320WXWCS00 | SF320WXWCS10 | SF320FGXFGCS00 | SF320FGXFGCS10 |
| 4" | SF420WXWCS00 | SF420WXWCS10 | SF420FGXFGCS00 | SF420FGXFGCS10 |

Split Flange Swivel Components

Split Flange Bearing Packs




| Size | Carbon Steel Part # |
|------|---------------------|
| 2" | 2SFBP |
| 3" | 3SFBP |
| 4" | 4SFBP |

Split Flange Nose Pieces

Feature

· 2 required per bearing pack



Seal Kits

Features

- · Kits contains: seal, PTFE retainer, carbon steel bolts
- · 1 required per bearing pack

