

Contractors EPDM Water Hose



Features

- Heavy-duty, crush-proof solid brass couplings with wrench grips
- Spiral synthetic cord reinforcement
- Black cover

Specifications

- Working pressure: 150 PSI
- Temperature range: -20°F to 180°F (-29°C to 82°C)

| Size       | EPDM Part # | Optional Qty |
|------------|-------------|--------------|
| 3/4" x 50' | CWH50       | 3            |

Rubber Vinyl Garden Hose



Features

- Extra tough, five-ply construction
- Exclusive, soft textured, abrasion-resistant green cover
- Dual reinforced, heavy-duty, flexibility, kink resistance
- Combines durability of rubber, easy handling of vinyl
- SEAL-TITE® leakproof coupling

Specifications

- Working pressure: 400 PSI
- Temperature range: 0°F to 140°F (-18°C to 60°C)

| Size        | Rubber Vinyl Part # | Optional Qty |
|-------------|---------------------|--------------|
| 5/8" x 25'  | SGH25               | 5            |
| 5/8" x 50'  | SGH50               | 5            |
| 5/8" x 75'  | SGH75               | 3            |
| 5/8" x 100' | SGH100              | 3            |

Premium EPDM Hose



Features

- Professional grade reinforcement provides maximum strength
- Heavy-duty flexibility
- Ultimate kink resistance
- SEAL-TITE® leakproof coupling
- Lead-free drinking water safe
- 40% lighter than standard rubber hose
- Black cover

Specifications

- Working pressure: 400 PSI
- Temperature range: -40°F to 165°F (-40°C to 74°C)

| Size        | EPDM Part # | Optional Qty |
|-------------|-------------|--------------|
| 5/8" x 50'  | PGH50       | 4            |
| 5/8" x 100' | PGH100      | 4            |

Flexogen® Hose



Features

- Heavy-duty, crush-resistant, full-flow brass couplings with a built-in washer for tight sealing
- Coils and handles easily in all weather
- Lightweight patented 8-ply construction
- Maximum kink resistance
- Flow guard plus protective collar resists kinks at faucet
- Polished surface resists abrasions, stains, and mildew
- Grey cover

| Size       | Flexogen® Part # |
|------------|------------------|
| 5/8" x 25' | FGH25            |
| 5/8" x 50' | FGH50            |