Pipe and Tube Clamps

Application

• Standard hydraulic applications, general pipe construction, electric cables, etc.

Features

- · Clamps are welded in place to secure the pipe or tubing
- Polypropylene cushions reduce wear due to vibration
- · Kit includes clamp with weld plate, cover plate, and bolts

Specifications

- Standard and twin series clamps are recommended for systems with less than 1500 PSI without dynamic loads
- Heavy duty clamps are recommended for systems with greater than 1500 PSI operating pressure

Standard Series

Pipe Nom. Bore/Tube O.D.	Length	Width	Height	Steel & Polypropylene Part #		
1/8" pipe	1.65"	1.18"	1.30"	HST02P		
1/4" pipe	1.89"	1.18"	1.54"	HST04P		
1/4" tube	1.65"	1.18"	1.30"	HST04T		
5/16" tube	1.65"	1.18"	1.30"	HST05T		
3/8" pipe	1.89"	1.18"	1.54"	HST06P		
3/8" tube	1.65"	1.18"	1.30"	HST06T		
1/2" pipe	2.17"	1.18"	1.61"	HST08P		
1/2" tube	1.89"	1.18"	1.54"	HST08T		
5/8" tube	1.89"	1.18"	1.54"	HST10T		
3/4" pipe	2.44"	1.18"	1.89"	HST12P		
3/4" tube	2.17"	1.18"	1.61"	HST12T		
7/8" tube	2.17"	1.18"	1.61"	HST14T		
1" pipe	2.91"	1.18"	2.52"	HST16P		
1" tube	2.17"	1.18"	1.61"	HST16T		
1-1/4" pipe	2.91"	1.18"	2.52"	HST20P		
1-1/4" tube	2.91"	1.18"	2.52"	HST20T		
1-1/2" pipe	3.46"	1.18"	2.83"	HST24P		
1-1/2" tube	2.91"	1.18"	2.52"	HST24T		
2" tube	3.46"	1.18"	2.83"	HST32T		





Twin Series

Pipe Nom. Bore/Tube O.D.	Length	Width	Height	Steel & Polypropylene Part #
1/8" pipe	1.46"	1.18"	1.36"	HTW02P
1/4" pipe	1.46"	1.18"	1.36"	HTW04P
1/4" tube	1.46"	1.18"	1.36"	HTW04T
5/16" tube	1.46"	1.18"	1.36"	HTW05T
3/8" pipe	2.17"	1.18"	1.42"	HTW06P
3/8" tube	1.46"	1.18"	1.36"	HTW06T
1/2" pipe	2.76"	1.18"	1.85"	HTW08P
1/2" tube	2.17"	1.18"	1.42"	HTW08T
5/8" tube	2.17"	1.18"	1.42"	HTW10T
3/4" pipe	3.35"	1.18"	2.05"	HTW12P
3/4" tube	2.76"	1.18"	1.85"	HTW12T
7/8" tube	2.76"	1.18"	1.85"	HTW14T
1" pipe	4.33"	1.18"	2.52"	HTW16P
1" tube	2.76"	1.18"	1.85"	HTW16T
1-1/4" pipe	4.33"	1.18"	2.52"	HTW20P
1-1/4" tube	4.33"	1.18"	2.52"	HTW20T
1-1/2" tube	4.33"	1.18"	2.52"	HTW24T

