

Global Type C Couplers

Coupler x Hose Shank

Features

- Interchanges with all products produced to A-A-59326D
 Nitrile rubber seals are standard

Size	A380 Permanent Mold Aluminum with Brass Handles Part #	ASTMC38000 Forged Brass Part #
1/2"	G50-C-AL ^{1,2}	G50-C-BR ^{1, 2}
3/4"	G75-C-AL ²	G75-C-BR ²
1"	G100-C-AL ²	G100-C-BR ²
1-1/4"	G125-C-AL	G125-C-BR
1-1/2"	G150-C-AL	G150-C-BR
2"	G200-C-AL	G200-C-BR
2-1/2"	G250-C-AL	G250-C-BR
3"	G300-C-AL	G300-C-BR
4"	G400-C-AL	G400-C-BR
5"	G500-C-AL ¹	G500-C-BR1
6"	G600-C-AL	
8"	G800-C-AL ¹	

Size	316 Investment Cast Stainless Steel Part #	A380 Permanent Mold Aluminum with Investment Stainless Handles Part #
1/2"	G50-C-SS ¹	
3/4"	G75-C-SS	
1"	G100-C-SS	
1-1/4"	G125-C-SS	
1-1/2"	G150-C-SS	G150-C-ALSI
2"	G200-C-SS	G200-C-ALSI
2-1/2"	G250-C-SS	
3"	G300-C-SS	G300-C-ALSI
4"	G400-C-SS	G400-C-ALSI
6"	G600-C-SS	



316 investment cast stainless steel

NOTE: See page 7 for Global Crimp Type C couplers

 $^{^{\, \}mathrm{l}}$ No standard exists for the 1/2", 5", and 8", and generally these sizes do not interchange with other manufacturers' products. products.
² Supplied with stainless steel handles