Application

 For control of air, water, oil, and gas in hose or pipe lines. For other services, please contact Dixon®

Features

sliding lock mechanism

- · Blow-out proof RPTFE stem
- Full and standard port valves are repairable

Materials

- Chrome-plated bronze ball
- Stainless steel sliding lock mechanism secures handle in open or closed position; can be padlocked opened or closed
- Plated steel handles and nuts with vinyl sleeves

Specification

Pressure rating: 600 PSI CWP; 150 PSI saturated steam

Female NPT	Port	Bronze
		Part #
1/4"	full	BBLV25
3/8"		BBLV38
1/2"		BBLV50
3/4"	standard	BBLV75
1"		BBLV100
1-1/4"		BBLV125
1-1/2"		BBLV150
2"		BBLV200

Bronze Ball Valves

Applications

• For air, water, oil, and gas service

Materials

- Chromium plated ball
- · RTFE seats and stuffing box ring

Features

- Blow-out proof stem
- Adjustable packing gland

Specification

- Pressure rating: 600 PSI
- Cold non-shock pressure rating: 150 PSI saturated steam

Male NPT x Female NPT	Port	Bronze Part #
1/2"	standard	BMV50
3/4"	standard	BMV75
1"	standard	BMV100

"Deadman" Spring Return Handle Brass Ball Valves

Features

- · Blow-out proof stem design
- Adjustable packing gland
- Spring return closes valve when not held open

Specification

- Operating torque approximately three times standard valve torque
- Pressure rating: 600 PSI CWP; 150 PSI saturated steam
- · Vacuum service to 29 inches Hg

Materials

- · Stainless steel lever
- Chromium plated ball
- · RTFE seats and stuffing box ring



