

Full Port Ball Valves with Locking Handle

Applications

- For use with water, oil, and gas

Features

- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve


Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket and thrust washer
- Plastic cover on handle

Specifications

- Temperature range: **-20°F to 356°F (-29°C to 180°C)**
- Pressure rating: 1/4" - 2" rated to **1000 PSI WOG (CWP)**
2-1/2" - 3" rated to **800 PSI WOG (CWP)**
100 PSI saturated steam

| Female NPT | Port | 316 Stainless Steel Part # |
|------------|------|----------------------------|
| 1/4" | full | SSLBV25 |
| 3/8" | | SSLBV38 |
| 1/2" | | SSLBV50 |
| 3/4" | | SSLBV75 |
| 1" | | SSLBV100 |
| 1-1/4" | | SSLBV125 |
| 1-1/2" | | SSLBV150 |
| 2" | | SSLBV200 |
| 2-1/2" | | SSLBV250 |
| 3" | | SSLBV300 |



Reduced Port Ball Valves with Locking Handle

Applications

- For use with water, oil, and gas

Features

- Lockable
- Blow-out proof stem design
- Not recommended as a throttling valve

Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer
- Plastic cover on handle

Specifications

- Temperature range: **-20°F to 356°F (-29°C to 180°C)**
- Pressure rating: **1000 PSI WOG; 100 PSI saturated steam**

| Female NPT | Port | 316 Stainless Steel Part # |
|------------|---------|----------------------------|
| 1/4" | reduced | SSLBV25SP |
| 3/8" | | SSLBV38SP |
| 1/2" | | SSLBV50SP |
| 3/4" | | SSLBV75SP |
| 1" | | SSLBV100SP |
| 1-1/4" | | SSLBV125SP |
| 1-1/2" | | SSLBV150SP |
| 2" | | SSLBV200SP |

