

Feature

• Ref SAE 130140

Reducer Hex Bushings

Male NPTF	Female NPTF	Brass			Lead-Free Brass ^{2, 3}
		Previous Part #	Part #	Optional Qty	Part #
1/4"	1/8"	HB1F2M	3730402C	100	3730402CLF
3/8"	1/8"	HB1F3M	3730602C	100	
	1/4"	HB2F3M	3730604C	100	3730604CLF
1/2"	1/8"	HB1F4M	3730802C	25	
	1/4"	HB2F4M	3730804C	50	3730804CLF
	3/8"	HB3F4M	3730806C	50	3730806CLF
3/4"	1/8"	HB1F6M	3731202C1	25	
	1/4"	HB2F6M	3731204C	25	
	3/8"	HB3F6M	3731206C	25	
	1/2"	HB4F6M	3731208C	25	3731208CLF
1"	1/4"	HB2F8M	3731604C1	10	
	3/8"	HB3F8M	3731606C1	10	
	1/2"	HB4F8M	3731608C	10	
	3/4"	HB6F8M	3731612C	10	



- ¹ SAE does not provide a standard for these sizes
- ² NSF®/ANSI 61 certified lead-free brass <=0.25% lead, Alloy C2745
- ³ Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant

NOTE: NPTF threads

AdaptersFemale NPTF x Male NPTF

Feature

• Ref SAE 130139

Female NPTF	Male NPTF	Brass		0 1 101	Lead-Free Brass ^{1, 2}
		Previous Part #	Part #	Optional Qty	Part #
1/8"	1/8"	RA1F1M	3750202C	100	
1/4"	1/8"	RA2F1M	3750402C	50	3750402CLF
	1/4"	RA2F2M	3750404C	50	3750404CLF
3/8"	1/8"	RA3F1M	3750602C	50	
	1/4"	RA3F2M	3750604C	50	3750604CLF
	3/8"	RA3F3M	3750606C	50	
1/2"	1/4"	RA4F2M	3750804C	25	
	3/8"	RA4F3M	3750806C	25	
	1/2"	RA4F4M	3750808C	25	3750808CLF
3/4"	3/8"	RA6F3M	3751206C	10	
	1/2"	RA6F4M	3751208C	10	
	3/4"	RA6F6M	3751212C	10	3751212CLF



- ¹ NSF®/ANSI 61 certified Lead-Free Brass <=0.25% lead, Alloy C2745
- ² Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant

NOTE: NPTF threads

Application Pump Adapters

· Used to convert BSP pump outlets to NPT

Feature

• Other sizes, configurations are available; contact Dixon®

Material

· Hard-coated, extruded 6061-T6 aircraft aluminum alloy

Female BSP	Male NPT	Aluminum Part #
1-1/2"	1-1/2"	AHA15BSP15T
2"	2"	AHA20BSP20T
2-1/2"	2-1/2"	AHA25BSP25T
3"	3"	AHA30BSP30T
4"	4"	AHA40BSP40T



NOTE: For additional information on pipe dimensions, please reference dixonvalve.com.