# Dixon® Type DA 45° Elbows

## Adapter x Coupler

### **Feature**

Nitrile rubber gasket standard, other gaskets available on pages 68 - 71



Size	356T6 Aluminum	316 Stainless Steel	Unplated Malleable Iron
	Part #	Part #	Part #
2"	200DA-45AL <sup>1</sup>	200DA-45SS1	
3"	300DA-45AL	300DA-45SS	
4"	400DA-45AL	400DA-45SS1	400DA-45MI
6"	600DA-45AL		


<sup>&</sup>lt;sup>1</sup> Part is produced as a welded fabrication

# **Dixon Type DD 45° Elbows**

# **Coupler x Coupler**

## **Feature**

Nitrile rubber gasket standard, other gaskets available on pages 68 - 71



<sup>&</sup>lt;sup>1</sup> Part is produced as a welded fabrication

# **Dixon Type DA 90° Elbows**

## Adapter x Coupler

### **Feature**

Nitrile rubber gasket standard, other gaskets available on pages 68 - 71



<sup>&</sup>lt;sup>1</sup> Part is produced as a welded fabrication

# **Dixon Type DD 90° Elbows**

## **Coupler x Coupler**

Nitrile rubber gasket standard, other gaskets available on pages 68 - 71

Size	356T6 Aluminum Part #	316 Stainless Steel Part #
2"	200DD-90AL	
3"	300DD-90AL	300DD-90SS1
4"	400DD-90AL	
6"	600DD-90AI	

Part is produced as a welded fabrication

# Type A 90° Elbows

## Adapter x Female NPT

• Pressure rating is based on the seal of the mating part, see ratings on page 20

Size	356T6 Aluminum Part #	316 Stainless Steel Part #
1-1/2"	150A-90AL	
2"	200A-90AL	200A-90SS <sup>1</sup>
3"	300A-90AL	300A-90SS
4"	400A-90AI	

<sup>&</sup>lt;sup>1</sup> Part is produced as a welded fabrication





<sup>&</sup>lt;sup>2</sup> EZ Boss-Lock design (not pictured)