Fire Hose, Fittings, and Accessories



Domestic Cast Angle Valves

Material

· Aluminum hand wheel

Specification

• Working pressure: 300 PSI at 70°F (21°C)

Approval

• UL listed and FM approved

Female x Male



Inlet Female NPT	Outlet Male Thread	Cast Brass Part #
	1-1/2" NST (NH)	AV150
1-1/2"	1-1/2" NPSH	AV150S
	1-1/2" NPT	AV150T
2-1/2"	2-1/2" NST (NH)	AV250
	2-1/2" NYFD	AV250NYFD ¹

¹ Supplied with red hand wheel



Female x Female

Inlet Female NPT	Outlet Female NPT	Cast Brass Part #	
1-1/2"	1-1/2"	AVF150	
2-1/2"	2-1/2"	AVF250	


Replacement Parts

Description	Part #
aluminum handwheel for 1-1/2" valve	AV150-W
aluminum handwheel for 2-1/2" valve	AV250-W
handwheel nut for 1-1/2" valve	AV150-N
handwheel nut for 2-1/2" valve	AV250-N
valve seal rubber for 1-1/2" valve	AV150-RBR
valve seal rubber for 2-1/2" valve	AV250-RBR

Dimensions

Size	Α	В	C closed	C open	D	F
1-1/2"	2-11/64"	2-7/32"	6-5/8"	7-21/32"	3-3/4"	2-13/16"
2-1/2"	3-3/16"	3-3/16"	9-1/4"	11″	5"	3-19/32"





- В →