NPT Threaded Caps

Features

- · Other sizes are also available
- 304 stainless steel fittings are also available, consult Dixon® for pricing and availability



300# iron



150# iron



150# galvanized iron



150# 316 stainless steel

Female NPT	300# Iron Part #	150# Iron Part #
1/8"		MICAP18
1/4"		MICAP25
3/8"		MICAP38
1/2"	300MICAP50	MICAP50
3/4"	300MICAP75	MICAP75
1"	300MICAP100	MICAP100
1-1/4"	300MICAP125	MICAP120
1-1/2"	300MICAP150	MICAP150
2"	300MICAP200	MICAP200
2-1/2"		MICAP250
3"		MICAP300
4"		MICAP400
5"		MICAP500
6"		MICAP600

Female NPT	150# Galvanized Iron Part #	150# 316 Stainless Steel Part #
1/8"		SSCAP18
1/4"		SSCAP25
3/8"		SSCAP38
1/2"	MICAP50G	SSCAP50
3/4"	MICAP75G	SSCAP75
1"		SSCAP10
1-1/4"		SSCAP12
1-1/2"		SSCAP15
2"	MICAP200G	SSCAP20

NPTF Pipe Caps

Feature

• Lead-free per NSF/ANSI 372



Female NPTF	Optional Qty	Lead-Free Brass ^{1, 2} Part #
1/8"	50	2130200CLF
1/4"	100	2130400CLF
3/8"	25	2130600CLF
1/2"	25	2130800CLF
3/4"	25	2131200CLF
1"	10	2131600CLF

¹ Lead-free Brass <=.25% lead, Alloy C27450

NOTE: For additional information on pipe dimensions please reference dixonvalve.com.

² Conforms To: Safe Water Drinking Act (SWDA) of Jan. 4, 2014; California AB1953; RoHS Compliant