### **Application**

· For use with petroleum and home heating oil hose



#### Feature

Prevents hose twisting or kinking

· · · · · · · · · · · · · · · · · · ·			
Male NPT	Shank Size	Bronze Part #	
1-1/2"	1-1/2"	1565U	
	Repair Kit		
Description		Part #	
replacement seal kit and retaining ring		1500SK	

# **Heavy Duty Hose Swivels**

#### **Features**

- Heavy duty internal thrust bearing and anti-friction seal design ensures swiveling at -40°F (-40°C)
- · Can be lubricated without disassembly by using the optional grease nipple kit below

#### **Specification**

• Male NPT x female NPT threaded connections



Male NPT	Female NPT	Bayloy Part #
1-1/4"	1-1/4"	SWMF125
1-1/2"	1-1/2"	SWMF150
2"	2"	SWMF200
	Repair Kits	

Description	Part #	
inlet swivel grease nipple kit (optional)	SWMF-RK1	
inlet swivel seal and wear kit	SWMF-RK22	
complete inlet swivel rebuild kit	SWMF-RK32	
2" FNPT replacement inlet swivel	SWMF-RK42	
1-1/2" FNPT replacement inlet swivel	SWMF-RK52	

# **Dixon® MannTek Hose Swivels**

## **Features**

- Allows the hose to relax to its natural rest position while allowing freedom of movement without adding torque stress at the point of connection
- · Simple design, low maintenance consists of two body halves, ball bearings, and a washer
- FKM seals standard, Chemraz<sup>®</sup> and Kalrez<sup>®</sup> optional; contact Dixon<sup>®</sup>

# **Specifications**

- Working pressure: 150 PSI
- Maximum temperature: 300°F (149°C)
- Male NPT x female NPT threaded connections

Size	316 Stainless Steel Part #	Aluminum Part #
3/4"	HS075SS	HS075AL
1"	HS100SS	HS100AL
1-1/2"	HS150SS	HS150AL
2"	HS200SS	HS200AL
3"	HS300SS	HS300AL
Λ"	220012H	HSANNAI

