# 150 lb. ASA Forged Flanges

#### **Sizes**

• 1" - 12"

## **Materials**

- Carbon steel
- 316 stainless steel

#### **Features**

- · Flush face: Lap Joint
- Raised face: Slip-On, NPT Threaded, and Weld Neck
- Lap joint is commonly called a "Van Stone" or a "floating flange"

## **Carbon Steel**

Size	Number of Bolts	Lap Joint Part #	Slip-On Part #	NPT Threaded Part #	Weld Neck Part #
1"	4	LJ100	S0100	T100	WN100
1-1/4"	4	LJ125	S0125	T125	WN125
1-1/2"	4	LJ150	SO150	T150	WN150
2"	4	LJ200	SO200	T200	WN200
2-1/2"	4	LJ250	SO250	T250	
3"	4	LJ300	SO300	T300	WN300
4"	8	LJ400	SO400	T400	WN400
5"	8	LJ500	SO500	T500	WN500
6"	8	LJ600	SO600	T600	WN600
8"	8	LJ800	S0800	T800	WN800
10"	12	LJ1000	S01000	T1000	WN1000
12"	12	LJ1200	S01200	T1200	

### 316 Stainless Steel

Size	Number of Bolts	Lap Joint Part #	Slip-On Part #	NPT Threaded Part #	Weld Neck Part #
1"	4	LJR100	SOR100	TR100	WNR10015
1-1/4"	4				WNR12515
1-1/2"	4	LJR150	SOR150	TR150	WNR15015
2"	4	LJR200	SOR200	TR200	WNR20015
3"	4	LJR300	SOR300	TR300	WNR30015
4"	8	LJR400	SOR400	TR400	WNR40015
5"	8				WNR50015
6"	8	LJR600	SOR600	TR600	WNR60015
8"	8				WNR80015
10"	12				WNR100015

# **Flange Gaskets**

#### **Features**

- Standard drop-ring type all 1/16" thick
- For flange dimensional information and diagrams please reference dixonvalve.com

Size	Neoprene Part #	Klingersil® C-4401 Part #		
1"	NG10	AG10		
1-1/4"	NG15	AG15		
1-1/2"	NG20	AG20		
2"	NG25	AG25		
2-1/2"	NG30	AG30		
3"	NG35	AG35		
4"	NG40	AG40		
5"	NG50			
6"	NG60	AG60		
8"	NG80	AG80		











(Use appropriate gaskets and bolts)




The Right Connection®




4 bolt





8 bolt



# **Flange Diagrams**







## **Dimensions**

Nominal Pipe Size	Flange O.D.	Thickness <sup>1</sup>	O.D. of Raised Face	Diameter of Bolt Circle	Number of Bolts	Diameter of Bolt Holes	Diameter of Bolts
1"	4-1/4"	9/16"	2"	3-1/8"	4	5/8"	1/2"
1-1/4"	4-5/8"	5/8"	2-1/2"	3-1/2"	4	5/8"	1/2"
1-1/2"	5"	11/16"	2-7/8"	3-7/8"	4	5/8"	1/2"
2"	6"	3/4"	3-5/8"	4-3/4"	4	3/4"	5/8"
2-1/2"	7"	7/8"	4-1/8"	5-1/2"	4	3/4"	5/8"
3"	7-1/2"	15/16"	5"	6"	4	3/4"	5/8"
4"	9"	15/16"	6-3/16"	7-1/2"	8	3/4"	5/8"
5"	10"	15/16"	7-5/16"	8-1/2"	8	7/8"	3/4"
6"	11"	1"	8-1/2"	9-1/2"	8	7/8"	3/4"
8"	13-1/2"	1-1/8"	10-5/8"	11-3/4"	8	7/8"	3/4"
10"	16"	1-3/16"	12 -3/4"	14-1/4"	12	1"	7/8"
12"	19"	1-1/4"	15"	17"	12	1"	7/8"

<sup>&</sup>lt;sup>1</sup> 1/16" raised face is included in the thickness