# **Data Sheet**

# **Compression Fittings**





### **Compression Fittings**

60C	Sleeve
60PT	Acetal Sleeve*

61C Nut 61CL Long Nut 62C Union

**Bulkhead Union** 62CBH Brass and SS Insert\* 63PT 66C Female Connector 68C Male Connector 164C/264C Union Tee 165C **Union Elbow** 169C/269C Male Elbow 170C Female Elbow 171C Male Run Tee 172C Male Branch Tee 176C Adapter Tee

179C 45° Elbow 639C Seal Plug

682C Straight Thru Tank Fitting

#### **Compliances**

177C

- · Meets functional requirements of SAE J512
- Reference: 060101BA, 060102BA, 060103BA, 060110, 060111,060115, 060201BA, 060202BA, 060203BA, 060401BA, and 060424BA

Female Branch Tee

· UL Listed for flammable liquids

# **Compatible Piping Products**

- · Annealed copper, aluminum, or thermoplastic
- \*Acetal Sleeves 60PT and Inserts 63PT allow for standard compression fittings to be used with industrial grades of thermoplastic tubing.

## **Dixon Brass**

40 Chestnut Ave, Westmont, IL, 60559 ph: 800.323.4440 fx: 800.628.7259 dixonvalve.com

# **Applications**

- Low and medium pressure tubing connection work where excessive vibration or tube movement is not involved. Long nut recommended for additional vibration resistance.
- · Non-potable water service

### **Materials**

- · Brass: alloy 360 and 230 for straight fittings
- · Brass: alloy 377 for forged shapes
- · Brass: Alloy 23000 low lead for 63PT
- 302SS or 304SS: for 63PT (3 sizes)

### **Specifications**

- Temperature: from -65°F (-54°C) to +250°F (121°C) with soft metal tubing and manufacturer's recommendations for thermoplastic tubing
- Working pressure at 73°F (23°C), refer to the following table:

PSI	Tube O.D.	Tube Wall
400	1/8"	.030"
400	3/16"	.030"
300	1/4"	.030"
300	5/16"	.032"
200	3/8"	.032"
200	1/2"	.032"
150	5/8"	.035"
100	3/4"	.035"
75	7/8"	.035"

# **Assembly Guide**

- Slide nut then sleeve onto tubing with thread end of nut facing out
- Insert tube into fitting ensuring that tube has bottomed out in the fitting body
- · Assemble nut to fitting body and hand-tighten
- · Wrench tighten per the following table

# Turns Required To Seal From Hand-Tight

<u> </u>					
	Fitting Size	Tube Size	60-Series with Soft Metal Tubing	60PT*-Series with Thermoplastic Tubing	
	2"	1/8"	1-1/4	-	
	3"	3/16"	1-1/4	-	
	4"	1/4"	1-1/4	2	
	5"	5/16"	1-1/4	2	
	6"	3/8"	2-1/4	2	
	8"	1/2"	2-1/4	2	
	10"	5/8"	2-1/4	2	
	12"	3/4"	2-1/4	2	
	14"	7/8"	2-1/4	-	

© 2023 DVCC • CFDS\_123