

Grooved Bolted Clamps

Features

- · Bolt torque: 20 ft. lbs.
- Precision casting and machined dimensions provide an exact fit and great appearance
- · Use of lock nuts prevents clamps from loosening in high vibration applications
- · Leak-tight connection
- Intended for tank truck applications only
- Unlike steel groove clamps that secure pipe ends with high clamp force against the tubing walls, the Dixon[®] bolted clamp takes the full bolt force and locks in the groove of the tube preventing distortion of the tube diameter
- · White nitrile rubber for use in dry bulk food applications

Specifications

- Temperature ratings for FKM-B 20°F to 300°F (-7°C to 149°C)
- Temperature ratings for Baylast[™] -20°F to 180°F (-29°C to 82°C)
- 2" pressure rating: 400 PSI
- 3" pressure rating: 170 PSI
- 4" pressure rating: 120 PSI

Approvals

- FKM-B rated for 100% biodiesel and ethanol
- Nitrile rubber rated for petroleum service, ethanol to E100, and biodiesel to B20
- Baylast rated for petroleum service, ethanol to E100, and biodiesel to B100

Size	Gasket Material	Aluminum Part #
2"	FKM-B	DBV-VB200
3"		DBV-VB300
4"		DBV-VB400
2"	Nitrile rubber	DBV-BN200
3"		DBV-BN300
4"		DBV-BN400
2"	Baylast	DBV-BL200
3"		DBV-BL300
4"		DBV-BL400
4"	white nitrile rubber	DBV-WB400

clamp with black nitrile rubber gasket Note: Supplied clamp gasket must be installed prior to use, ships separately.

Dixon Bayco[®]

7280 Union Centre Blvd West Chester, Ohio 45014 ph: 513.874.8499 fx: 513.874.8399 **dixonvalve.com**

© 2022 DVCC • GBC_522