



The Right Connection®

Introducing

Genuine Betts Wet-R-Dri™ Valve

Easily mounted in any position



Application:

- Designed for handling liquid, gaseous or dry products

Features:

- Body: lightweight extruded aluminum
- Disc: FKM B
- Handle location provides smooth operation
- Has a positive stop in the open and closed position
- Detent spring and ball assist in holding the disc in the open and closed position
- TTMA flange recommended standards
- Opens by turning hand ¼ turn counter clockwise
- Temperature range: 0°F to 400°F (-17.7°C to 204.4°C)
- Maximum working pressure: 75 PSI

Size	Description	Part #
3"	TTMA Wet-R-Dri™ valve manually operated detent handle	WD301ALVB
3"	TTMA Wet-R-Dri™ valve manually operated metering handle	WD304ALVB
4"	TTMA Wet-R-Dri™ valve manually operated detent handle	WD401ALVB
4"	TTMA Wet-R-Dri™ valve manually operated metering handle	WD404ALVB

Dixon Bayco

800 High Street • Chestertown, MD 21620
 ph 800.355.1991 • fx 800.283.4966
dixonvalve.com

Dixon Group Canada Limited

2315 Bowman Street • Innisfil, Ontario L9S 3V6
 phone: 800.355.1991 • fax: 877.436.6251
canada.dixonvalve.com