



The Right Connection®

# Black Liquor Hose Assemblies

For use in severe conditions found in the pulp and paper industry



### Application:

- used to convey Black Liquor in applications where heat and abrasion are a concern such as the pulp and paper industry

### Features:

- specification: 800E
- multiple layers of 1000°F rated heat resistant insulation
- temperature rating depends on specific application, consult Dixon for details

### Materials:

- tube: Butyl blend
- reinforcement: wire braid
- cover: EPDM
- GSM Ball Joint Armor: galvanized steel or stainless steel

### Sizes:

- ½" through 3"

Hose Dimension		Minimum Bend Radius	PSI		Approximate Weight / Ft. Lbs.
ID	Approximate OD		Working	Burst	
½"	1-15/64"	3"	250	2500	1.25
¾"	1-34/64"	4½"	250	2500	2.0
1"	1-54/64"	5"	250	2500	2.25
1¼"	2-8/64"	6"	250	2500	3.0
1½"	2-26/64"	7"	250	2500	3.5
2"	3"	10"	250	2500	4.5
2½"	3-24/64"	13"	250	2500	6.25
3"	4-9/64"	16"	250	2500	7.5

connect with us on



## Dixon Specialty Products

ph 888.226.4673 • fx 410.778.1958  
 225 Talbot Blvd. • Chestertown, MD 21620  
[dixonvalve.com](http://dixonvalve.com)

scan to visit our website

