

Turbo Nozzles

Features:

- 15° spray angle
- maximum temperature: **195°F (91°C)**
- ceramic orifice

Nozzle Size	Description	Orifice	Maximum Working PSI	Part #
4.0	¼" female inlet, dk. green	1.30 mm	<b>3,625</b>	<b>AL-TPR25-30</b>
5.5 - 6.0	¼" female inlet, purple	1.50 mm	<b>3,625</b>	<b>AL-TPR25-50</b>
7.0 - 7.5	¼" female inlet, grey	1.70 mm	<b>3,625</b>	<b>AL-TPR25-70</b>
4.0	¼" female inlet, dk. green	1.30 mm	<b>5,075</b>	<b>AL-TPR35-30</b>
5.5	¼" female inlet, purple	1.50 mm	<b>5,075</b>	<b>AL-TPR35-50</b>
6.5	¼" female inlet, grey	1.70 mm	<b>5,075</b>	<b>AL-TPR35-70</b>



Nozzle Holders

Feature:

- maximum temperature: **300°F (149°C)**

Description	Flow (GPM)	Working PSI	Part #
adjustable hi/low nozzle holder with nozzle protector, ¼" female inlet and outlet	<b>7.8</b>	<b>3,650</b>	<b>AL414</b>
change over nozzle, ¼" female inlet, 2 each ¼" female outlets	<b>8</b>	<b>2,900</b>	<b>AL416</b>



AL414



AL416

Inlet Filter for Turbo Nozzles

Features:

- ¼" female inlet, ¼" male outlet
- maximum temperature: **212°F (100°C)**
- 100 mesh filter

Description	Flow (GPM)	Working PSI	Part #
stainless steel, inlet water filter	<b>8</b>	<b>5,000</b>	<b>AR3500</b>



Balance Release Valve

Features:

- working PSI: **4,000 PSI**
- maximum temperature: **195°F (90.6°)**
- GPM: **6.6**
- inlet/outlet: ⅜" female NPT
- bypass: ⅜" female NPT

<i>Brass</i>
Part #
<b>AL702</b>



Water Broom

Features:

- working PSI: **4,000 PSI**
- ¼" quick connect plug

Description	Length	Stainless Steel Part #
4 nozzle broom	16"	<b>AR-BROOM16</b>

