

Dixon™ Piston Intake Relief Valves

Features:

- standard with a 30° elbow (permitting smoother water flow), adjustable relief valve, retractable knob on hand wheel and air bleed off
- permits safe controlled flow to the intake pump and can also be used to draft
- available with Storz or threaded combination
- 9 easy turns open and close the valve
- without relief valve **280 PSI** at 70°F (21°C), without relief valve
- 4½" minimum waterway
- finish anodized throughout - minimum thickness 0.001"
- relief valve - double spring, cartridge type, adjustable from **50 to 200 PSI**



Storz	Female Swivel NST (NH)	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
4"	4"	FSGR440F	\$3951.85	12"	8"	17"
4"	4½"	FSGR445F	3951.85	12"	8"	17"
4"	5"	FSGR450F	3951.85	12"	8"	17"
4"	6"	FSGR460F	3951.85	12"	8"	17"
5"	4"	FSGR540F	3951.85	12"	8"	17"
5"	4½"	FSGR545F	3951.85	12"	8"	17"
5"	5"	FSGR550F	3951.85	12"	8"	17"
5"	6"	FSGR560F	3951.85	12"	8"	17"



Male NST (NH)	(2)Female NST (NH) Swivel	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
4"	4"	FMGR40F40F	\$3951.85	12"	8"	17"
4"	4½"	FMGR40F45F	2863.65	12"	8"	17"
4"	5"	FMGR40F50F	2863.65	12"	8"	17"
4"	6"	FMGR40F60F	3951.85	12"	8"	17"
4½"	4"	FMGR45F40F	3951.85	12"	8"	17"
4½"	4½"	FMGR45F45F	3951.85	12"	8"	17"
4½"	5"	FMGR45F50F	2863.65	12"	8"	17"
4½"	6"	FMGR45F60F	3951.85	12"	8"	17"
5"	4"	FMGR50F40F	2978.20	12"	8"	17"
5"	4½"	FMGR50F45F	2978.20	12"	8"	17"
5"	5"	FMGR50F50F	3951.85	12"	8"	17"
5"	6"	FMGR50F60F	3951.85	12"	8"	17"
6"	6"	FMGR60F60F	3951.85	12"	8"	17"

- all measurements include handles

P



PV-HDWHL

Replacement Parts

Description	Part #	Price
handwheel and knob	PV-HDWHL	\$255.00
knob only	PV-KNOB	177.75